


MILLERS & PROCESSORS OF BASE MINERALS




Approved By: EJ Wenger
Compiled By: D. Prevoo

Doc No. : DS 015
Rev No. : 05

Date: 03 March 2014
Page 1 of 1

Data Sheet



Product: Red Iron Oxide
Grades: EXPORT

CHEMICAL ANALYSIS %

<i>Typical:</i>	Fe	62.95%
	Fe₂O₃	90.70%
	FeO	80.95%
	Fe metal	0.03%
	Al ₂ O ₃	2.0%max
	SiO ₂	6.0 %max
	P	0.065% max
	S	0.032 %max

PHYSICAL PROPERTIES:

pH:-	7.85
Dry Bulk Density:-	1.8 grams/cm ³ Tapped.
Particle Size:-	+ 45µm 5.0% max
Moisture	2.5% max

APPLICATION:

Colourant for glass, ceramics and cement. Jewellers rouge.
Nitrogen inhibitor in Green-sand Foundry sands.
Polishing powders and waxes. Filler inorganic substances.
Paint industry – primer paints for metal and wood.

PACKING:

Packed in 3 ply 40kg paper bags.

The information and recommendations in this product data sheet are based on data we believe to be reliable. They are offered in good faith, but do not imply any warranty or performance guarantee, as conditions and methods of use of our products are beyond our control. As such, African Pegmatite Company South Africa makes no express or implied warranties of any kind with respect to this product, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.

We recommend that the user determine whether the products and the information given are appropriate, and that the suitability and performance of our products are appropriate by testing with its own equipment. Specifications are subject to change without notice.

The information and recommendations given in this product data sheet should not be understood as a recommendation for the use of our products in violation of any patent or as a license to use any patents of the African Pegmatite Company South Africa.

Tel: +27 16 362-0600/4 Fax: +27 16 362-1239 Website: www.mineralmilling.com

